

# DUROPROOF™ M17

## Penetrating Sealer for Asbestos Cement Roof

*DUROPROOF™ M17 is a solvent based polymeric sealer specifically designed to penetrate, bind and saturate the surface of weathered asbestos cement roof sheeting. Once cured the surface becomes a stable adhesive substrate for the application of Duro Mastic™AC or Duro Mastic™ SR, long life acrylic membrane coating.*

### PRINCIPLE CHARACTERISTICS

- Single component
- Simple application
- Excellent penetration and adhesion
- Seamless—no joints
- No need to remove asbestos roof
- Does not support fungus growth

### Use Areas

- Weathered asbestos cement roof sheets
- Fibrous cement sheeting



### PACKAGING

- 20 Litres

### APPLICATION:

Clean the surface of all debris, moss and other loose materials taking care not to disturb the asbestos surface. Apply diluted **Duro Prep Anti Fungal Concentrate** and allow to dry.

Apply 2-3 coats of **Duroproof™M17** allowing 6-8 hours between coats. Ensure the surface is fully saturated. Allow 48 hours before top coating with **Duro Mastic™ AC or SR**. Take adequate precautions to prevent overspray damage.

### PRECAUTIONS:

Do not apply below 10°C or above 30°C. Avoid contact with skin and eyes. Provide adequate ventilation. Isolate sources of ignition during storage and application.

**Refer to Durotech MSDS prior to use.**

### CLEANING:

**Xylene** whilst wet. Commercial paint strippers once dry.

### GENERAL

Colour	Clear
Weather Resistance	Excellent, when top coated with Duro Mastic™AC, or SR
Service Life	8-10 years when top coated with Duro Mastic™AC, or SR
Dry time	Approx 2 hours @ 25° C
Recoat	Approx 6 hours @ 25° C
Top coat	3 days @ 25° C
Coverage	1-3 Litres /m <sup>2</sup> depending on substrate porosity
Solids content	43% by volume
Shelf Life	12 months in unopened containers stored at 20° C

**Durotech Industries** 14 Essex Street, P.O Box 5092, Minto, NSW 2566  
**Telephone: +61 2 9603 1177 Fax: +61 2 9603 3796 Technical 1300 791 177**  
 Email: sales@durotechindustries.com.au Web: www.durotechindustries.com.au



*The information provided in this technical bulletin is as correct in detail as possible and is intended to give a fair description of the product and its capabilities. In practice, the substrate and environmental conditions vary widely, making it essential for the user to determine the products suitability for a particular application and that the product is not used beyond its physical limitations. The product is guaranteed providing that it is applied in accordance with the manufacturer's instructions as stated in this data sheet and any relevant Standard or Code and provided that the building and installation is structurally sound. Durotech terms and conditions of sale apply.*