

# **DUROTECH BITUMEN PRIMER**

## **Solvent based bitumen primer**

*Durotech Bitumen Primer is an industrial bitumen primer that can be used as an economical coating to protect timber, concrete, masonry and metal surfaces from oxidization, water, sunlight, chemicals and weather exposure.*

*Durotech Bitumen Primer has good water, acid and alkali resistance.*

### **USE AREAS**

- Priming dry concrete decks (before application of bitumen sheet membrane)
- Protection of galvanised iron gutters, downpipes, and metal for corrosion protection
- As an adhesive to adhere malthoid to metal
- All bituminous surfaces for moisture protection.

### **APPLICATION**

All surfaces must be clean, dry and free from grease, oils, waxes and loose materials. New galvanised iron must be allowed to weather for at least six months prior to application. When used as a protective coating, use directly from the container with a broom, brush or spray (55 kPa pressure in pot and 275 kPa pressure at gun.)

### **PACKAGING**

- 20 Litre

### **GENERAL**

Colour	Black
Dry Time	12-24 hours @ 25°C
Flash Point	Flammable-Flash Point 32°C
Coverage on concrete	8m <sup>2</sup> /litre approx
Coverage on metal	10m <sup>2</sup> /litre approx
Clean Up	Clean tools and equipment with mineral turps
Shelf Life	12 months in sealed containers stored at 20°C

**Durotech Industries** 14 Essex Street, P.O Box 5092, Minto, NSW 2566  
**Telephone: +61 2 9603 1177 Fax: +61 2 9603 3796 Technical: 1300 791 177**  
 Email: sales@durotechindustries.com.au Web: www.durotechindustries.com.au



**DUROTECH**

*The information provided in this technical bulletin is as correct in detail as possible and is intended to give a fair description of the product and its capabilities. In practice, the substrate and environmental conditions vary widely, making it essential for the user to determine the products suitability for a particular application and that the product is not used beyond its physical limitations. The product is guaranteed providing that it is applied in accordance with the manufacturer's instructions as stated in this data sheet and any relevant Standard or Code and provided that the building and installation is structurally sound. Durotech terms and conditions of sale apply.*