

DURO MASTIC™ P15

WET AREA MEMBRANE

AS4858:2004 & AS3740:2004 compliant, CLASS III Membrane suitable for under tile waterproofing.

DURO MASTIC™ P15 is a modified acrylic urethane membrane. **DURO MASTIC™ P15** is a tough, flexible waterproof membrane with exceptional elongation and elasticity. It will expand and contract under normal substrate movement. It is supplied as a thixotropic liquid, that is easily applied to both vertical and horizontal surfaces. The formulation is designed to ensure a quick tack free time and fast cure, with a high solids content and excellent durability. **DURO MASTIC™ P15** passes the test requirements of AS 4858:2004 and conforms with the requirements of AS 3740 "Waterproofing of Wet Area's within Residential Buildings"-2004.



PRINCIPAL CHARACTERISTICS

- Water based, environmentally friendly
- Very fast drying
- Low VOC, <7g/Litre [APAS Guidelines]
- Industry leading solids content (>60% by volume)
- AS4858:2004 testing confirms durability is 200% greater than required
- Excellent movement and crack bridging capability (>800% elongation)
- Compatible with most building materials
- Does not bleed or leech oils

DURABLE WATERPROOFING SOLUTIONS

Durotech Industries 14 Essex Street P.O Box 5092 Minto NSW 2566

Telephone: +61 2 9603 1177 Fax: +61 2 9603 3796

Technical 1300 791 177

Email: sales@durotechindustries.com.au

Web: www.durotechindustries.com.au

