

DUROTECH ARW

Water Based Primer

DUROTECH ARW is a single component water based primer used to prime concrete, masonry and fibre cement sheeting surfaces. When dry, it forms a pink sealed surface suitable for the application of water based membranes.

The pink colouring generally indicates priming has been undertaken, thereby facilitating Q.A..

PRINCIPLE CHARACTERISTICS USE AREAS

- Water based
- Environmentally friendly
- Non Toxic
- Ease of use
- Low odour
- Simple to apply
- Primer for water based membranes internally
- Primer for Durohesive™ internally

APPLICATION

All surfaces to be sound and clean; concrete to be free of efflorescence and contamination. Apply when temperature is above 8°C. Use a brush or roller for application. Clean equipment with water before it dries.

COVERAGE

- Smooth Surface: 6-8 m² / L
- Rough / Porous Surface: 3 -4 m² / L

PACKAGING

- 20 Litres
- 4 Litres

GENERAL

- Colours Pink or clear
- Touch Dry 30 minutes at 25°C
- Shelf Life 1 year stored in unopened container at 20°C

NOTE: Durotech ARW used to be called Duroprime & Duromastic ARW

Durotech Industries 14 Essex Street, P.O Box 5092, Minto, NSW 2566
Telephone: +61 2 9603 1177 Fax: +61 2 9603 3796 Technical: 1300 791 177
 Email: sales@durotechindustries.com.au Web: www.durotechindustries.com.au


DUROTECH

The information provided in this technical bulletin is as correct in detail as possible and is intended to give a fair description of the product and its capabilities. In practice, the substrate and environmental conditions vary widely, making it essential for the user to determine the products suitability for a particular application and that the product is not used beyond its physical limitations. The product is guaranteed providing that it is applied in accordance with the manufacturer's instructions as stated in this data sheet and any relevant Standard or Code and provided that the building and installation is structurally sound. Durotech terms and conditions of sale apply.