

DuroTorch BITUMEN PRIMER

SOLVENT BASE BITUMEN PRIMER

Technical Data Sheet

Durotech Bitumen Primer is an industrial bitumen primer that can be used as an economical coating to protect timber, concrete, masonry and metal surfaces from oxidization, water, sunlight, chemicals and weather exposure. Durotech Bitumen Primer has good water, acid and alkali resistance.

USE AREA

- Priming dry concrete decks (before application of bitumen sheet membrane)
- Protection of galvanised iron gutters, downpipes, and metal for corrosion protection
- As an adhesive to adhere malthoid to metal
- All bituminous surfaces for moisture protection.

APPLICATION

All surfaces must be clean, dry and free from grease, oils, waxes and loose materials. New galvanised iron must be allowed to weather for at least six months prior to application. When used as a protective coating, use directly from the container with a broom, brush or spray (55 kPa pressure in pot and 275 kPa pressure at gun.)

PACKAGING

20 Litre

GENERAL INFORMATION

Color	Black
Dry Time	12-24 hours @ 25°C
Flash Point	Flammable – Flash Point 32°C
Coverage on concrete	8m ² /litre approx.
Coverage on metal	10m ² /litre approx
Clean Up	Clean tools and equipment with mineral turps
Shelf Life	12 months