



DUROPROOF™ BLF

FIBRE REINFORCED ROOF AND GUTTER LINING

DUROPROOF™ BLF is a fibreglass reinforced roof repair compound used to maintain and repair most roofs and gutters. DUROPROOF™ BLF is ideal for leaking box gutters, even emergency repairs in rain. DUROPROOF™ BLF forms a flexible fibre reinforced waterproof lining to all common building materials-metal, asbestos, slate, felt, asphalt, concrete, wood and plastic.

PRINCIPLE CHARACTERISTICS

- ◆ Resistant to weathering, waterproof
- ◆ Simple application
- ◆ Flexible, fast cure
- ◆ Long life, cost effective

USE AREA

- ◆ Maintenance and repair of metal or fibre / asbestos roofs, gutters, flashings
- ◆ Concrete roof decks and concrete gutters
- ◆ Retaining walls, tanking and metal flashings

PACKAGING

- ◆ 10 Litre
- ◆ 4 Litre

APPLICATION

Thoroughly clean and remove all loose dirt, rust, oil, flaking paint to give a sound surface. Apply DUROPROOF™ BLF liberally by brush and roller spreading the compound to a thickness of approx 1.5-2.0mm, taking care to work the compound well into the surface. Spread evenly before the material begins to dry. Two coats may be necessary to ensure an adequate dry film thickness, particularly on rusted surfaces. Rust holes and splits are repaired by laying fibreglass into the first coat, then applying a further coat.

TECHNICAL INFORMATION

Colour	Black
Weather Resistance	Very good. Surface will chalk slightly with exposure. For improved U.V. Protection, top coat with acrylic or aluminium paint.
Dry Time	Touch dry 40mins @ 25°C
Re-Coat	After 40mins @ 25°C
Coverage	2 coats each at 0.75ltrs/m ² [1.3m ² /Litre]
Wet Film Thickness	Per coat 0.75mm thick
Dry Film Thickness	1.0mm total
Solids Content	59%
Shelf Life	1 year in unopened container stored @ 20°C

CLEAN UP

Use mineral turps

PRECAUTIONS

During application, wear protective clothing, ensure adequate ventilation and eliminate ignition sources. Highly flammable in wet state. Refer Durotech MSDS prior to use.



14 Essex Street, P.O Box 5092, Minto, NSW 2566

+61 2 9603 1177

+61 2 9475 5059

sales@durotechindustries.com.au

www.durotechindustries.com.au