PRODUCT DATA SHEET

DUROTECH FLASHING TAPE SELF ADHESIVE



Waterproofing Joint Tape

DESCRIPTION

A hydrophobic non-woven polypropylene fleece laminated to a grey pressure sensitive butyl adhesive, supplied on a pre-slit extended filmic release liner.

Application

Designed to create permanent visco-elastic seals on the wall/floor interface and around drainage apertures in walls and floors. Being pressure sensitive there is no curing time for the tape, so liquid waterproofing membrane may be layed immediately onto the non-woven fleece surface. The product is for use in all wet areas such as kitchens, bathroom, showers, external balconies, roof joins etc. The product offers major benefits in that it contains no volatile organic content, is highly resistant to detergents and bleaches and is compatible with all commonly used sealants

GENERAL TECHNICAL DATA

Tape Thickness	1.0mm
Non-woven polypropylene fibre mass	50 g/M ²
Resistance to break Longitudinal Perpendicular	18 N/cm 13 N/cm
Peel Adhesion	> 4 N/cm
Service Temperature	-30°C to 80°C

Roll Size

• 80mm x 15 Metre

Surface Preparation

Surfaces should be clean, dry and free from surface contaminants prior to application. Firm pressure should be applied across the entire surface and the use of a pressure roller is recommended. The split liner allows for easy application and it is recommended that application be carried out between 5°C and 40°C.











