

DUROMASTIC ARW

WATERBASED PRIMER



DESCRIPTION

Duromastic ARW is a single component water based primer used to prime concrete, masonry and fibre cement sheeting surfaces. When dry, it forms a pink sealed surface suitable for the application of water based membranes.

FEATURES

- Fast drying, enabling membrane application within 30 minutes
- Water based
- Environmentally friendly
- Non toxic
- Ease of use
- Low odour
- Simple to apply

USE AREA

- Primer for water based membranes internally

PACKAGING

- 15 Litre
- 4 Litre

TECHNICAL INFORMATION

Colour	Pink or clear
Touch dry	30 minutes at 25°C
VOC	37 grams/litre
Shelf life	1 year stored in unopened container at 20°C

APPLICATION

All surfaces to be sound and clean; concrete to be free of efflorescence and contamination. Do not Apply when temperature is above 30° Celsius. Use a brush or roller for application. Clean equipment with water before it dries.

APPLICATION

- Smooth surface: 6-8 m²/L
- Rough / Porous Surface: 3 -4 m²/L



Precautions

- Do not use on glass or glazed surfaces.
- Do not apply over curing compounds, wax/oily surface, fibreglass, plastic or silicone treated surfaces.
- Not to be used as primer for areas with rising moisture or negative hydrostatic pressure
- Not to be applied over raw steel or metals unless otherwise specified in this data sheet.
- Although this product is non hazardous and water based, contents should not be swallowed or inhaled. In case of eye contamination, rinse with clean water and seek medical advice.
- Material Safety Data sheet (MSDS) available.
- For further information about this product contact technical department of Durotech Industries.

Notes

It is recommended before commencing the application; that adhesion of products to be used (e.g. primers, membranes, coatings adhesives etc) is tested over a typical area of the prepared surface to ensure satisfactory adhesion. It is the responsibility of the applicator to carry this out and accept the substrate suitability before any application starts. Duromastic Industries offers a service for pre testing adhesion to surfaces for large commercial areas or unusual substrates. For further details contact Durotech Industries.

Details contained in product data sheets are general. For any situation or items not covered in this data sheet, it is the responsibility of the applicator to check with Durotech Technical Services before commencing the application. A written confirmation will then be issued by Durotech Technical Services.

Durotech Industries

VICTORIA

34 Indian Drive Keysborough
Victoria 3173

Tel: 1300 434 272

sales@durotechindustries.com.au
www.durotechindustries.com.au

NEW SOUTH WALES

14 Essex st, Minto, Sydney
NSW 2566

Tel: 1300 434 272

sales@durotechindustries.com.au
www.durotechindustries.com.au

QUEENSLAND

16 Export Drive Molendinar,
Gold Coast 4214

Tel: 1300 434 272

sales@durotechindustries.com.au
www.durotechindustries.com.au

SOUTH AUSTRALIA

348 Richmond Road
Netley Australia

Tel: 1300 434 272

sales@durotechindustries.com.au
www.durotechindustries.com.au

"This document, including any attached files, is strictly confidential and intended solely for the use of the individual or entity to which it is addressed. Durotech Industries prohibits the right to publish, copy, distribute or disclose any information contained in this document, or its attachments, by any party other than the intended recipient. If you have received this document in error please notify the sender and delete it from your system no employee or agent is authorised to conclude any binding agreement or make any representation on behalf of Durotech Industries. The views or opinions presented in this document are solely those of the author and do not necessarily represent those of Durotech Industries, except where the sender expressly, and with clear authority, states them to be the views of Durotech Industries. Durotech Industries accepts no liability for any loss or damage (direct or indirect or consequential) arising from the use of or in connection with this document and any attachments and suggests that the recipient check this document and any attached files for the presence of viruses."

