

TECHNICAL DATA SHEET

DUROSHEET BGW STICKY TAPE

TECHNICAL INFORMATION

Item	Proposed Spec	Test method
Low temperature flexibility (-25°C)	No crack	GB 23457 – 2009
Shear strength (N/mm)	5.0	GB/T 328.23
Peel strength to PE film (N/mm)	0.8	JC863-2000
Peel Strength to concrete (N/mm)	0.8	JC863-2000





14 Essex Street, P.O Box 5092, Minto, NSW 2566

+61 2 9603 1177

♣ +61 2 9475 5059

sales@durotechindustries.com.au

www.durotechindustries.com.au

The information provided in this data sheet is correct at the time of printing (albeit is subject to change at any time) and is intended to give a simple description of the product and its capabilities. In practice, the substrate, intended surface to be treated and environmental conditions vary widely, making it essential for the user to determine the products suitability for a particular application and to ensure that the product is not used beyond its physical limitations. If in doubt contact the manufacturer. The product will perform as described herein provided it is applied in accordance with the manufacturer's instructions as stated in this data sheet and provided that the building and installation is structurally sound and the application is carried out competently. Durotech terms and conditions of sale apply.

Version: DuroSheet BGW Sticky Tape V01 Date: JUNE2018 Page 1 of 1