



DUROTECH ARW

WATER BASED PRIMER

DUROTECH ARW is a single component water based primer used to prime concrete, masonry and fibre cement sheeting surfaces. When dry, it forms a pink sealed surface suitable for the application of water based membranes.

PRINCIPLE CHARACTERISTICS

- ◆ Water based
- ◆ Environmentally friendly
- ◆ Non Toxic
- ◆ Ease of use
- ◆ Low odour
- ◆ Simple to apply

USE AREA

- ◆ Primer for water based membranes internally

APPLICATION

All surfaces to be sound and clean; concrete to be free of efflorescence and contamination. Apply when temperature is above 8°C. Use a brush or roller for application. Clean equipment with water before it dries.

COVERAGE

- ◆ Smooth Surface: 6-8 m² / L
- ◆ Rough / Porous Surface: 3 -4 m² / L

PACKAGING

- ◆ 20 Litres
- ◆ 4 Litres

TECHNICAL INFORMATION

Colours	Pink or clear
Touch Dry	30 minutes at 25°C
VOC	37 grams/litre
Shelf Life	1 year stored in unopened container at 20°C

NOTE: Durotech ARW used to be called Duroprime & Duromastic ARW



14 Essex Street, P.O Box 5092, Minto, NSW 2566

+61 2 9603 1177

+61 2 9475 5059

sales@durotechindustries.com.au

www.durotechindustries.com.au