

PRODUCT DATA SHEET

DUROTECH FLASHING TAPE SELF ADHESIVE

Waterproofing Joint Tape



DESCRIPTION

A hydrophobic non-woven polypropylene fleece laminated to a grey pressure sensitive butyl adhesive, supplied on a pre-slit extended filmic release liner.

Application

Designed to create permanent visco-elastic seals on the wall/floor interface and around drainage apertures in walls and floors. Being pressure sensitive there is no curing time for the tape, so liquid waterproofing membrane may be laid immediately onto the non-woven fleece surface. The product is for use in all wet areas such as kitchens, bathroom, showers, external balconies, roof joins etc. The product offers major benefits in that it contains no volatile organic content, is highly resistant to detergents and bleaches and is compatible with all commonly used sealants.

Roll Size

- 80mm x 15 Metre

Surface Preparation

Surfaces should be clean, dry and free from surface contaminants prior to application. Firm pressure should be applied across the entire surface and the use of a pressure roller is recommended. The split liner allows for easy application and it is recommended that application be carried out between 5°C and 40°C.

GENERAL TECHNICAL DATA

Tape Thickness 1.0mm

Non-woven polypropylene fibre mass 50 g/M²

Resistance to break
Longitudinal 18 N/cm
Perpendicular 13 N/cm

Peel Adhesion > 4 N/cm

Service Temperature -30°C to 80°C

DUROTECH INDUSTRIES

"This document, including any attached files, is strictly confidential and intended solely for the use of the individual or entity to which it is addressed. Durotech Industries prohibits the right to publish, copy, distribute or disclose any information contained in this document, or its attachments, by any party other than the intended recipient. If you have received this document in error please notify the sender and delete it from your system immediately. No employee or agent is authorised to conclude any binding agreement or make any representation on behalf of Durotech Industries. The views or opinions presented in this document are solely those of the author and do not necessarily represent those of Durotech Industries, except where the sender expressly, and with clear authority, states them to be the views of Durotech Industries. Durotech Industries accepts no liability for any loss or damage (direct or indirect or consequential) arising from the use of or in connection with this document and any attachments and suggests that the recipient check this document and any attached files for the presence of viruses."

